

इंडियन फारमर्स फर्टिलाइनर को आपरेटिव लिमिटेड INDIAN FARMERS FERTILISER COOPERATIVE LIMITED

Ref: AP/Tech/Env-Audit/2024-25

Date: 27.08.2025

To,

The Member Secretary. U. P. Pollution Control Board. TC 12v. Vibhuti khand. Gomti Nagar, Lucknow-226010

Subject: Environmental Statement for the year 2024-25.

Dear Sir,

We are submitting herewith the Environmental Statement of our unit for the vear 2024-25 under rule 14 of Environment (Protection) Rule. 1986 for your kind reference

Regards,

Your's faithfully For IFFCO Aonla Unit

(Satyajit Pradhan) Sr. General Manager

Encls: As Above.

Copy to:

- 1. The Member Secretary, Central Pollution Control Board, East Arjun Nagar, CBD Cum Office Complex, Sahadara, Delhi-110033.
- 2. The Incharge, Central Pollution Control Board, Regional Office (Central Zone) PICUP Bhawan, Ground Floor, B-Block, Vibhuti Khand, Gomti Nagar, Lucknow-226010
- 3. The Regional Officer, U.P. Pollution Control Board, 1219/1, E-Block, Rajendra Nagar, Bareilly-243122
- 4. The Director, Ministry of Environment & Forests, Regional Office, Kendriya Bhavan, 5th Floor, Sector-H, Aliganj, Lucknow - 2324047



आँवला इकाई, पॉल पोथन नगर, पो. आ. इफको टाऊनशिप, जिला बरेली – 243403 (उ. प्र.) Aonla Unit, PAUL POTHEN NAGAR, P.O. IFFCO TOWNSHIP, Distt. Bareilly - 243403 (U.P.)

Unit Head Office: 0581-2404003 Finance: 0581-2404030 Technical: 0581-2404018

Pers & Admn: 0581-2404064

Production: 0581-2404004

Maintenance: 0581-2404012 Utilities: 0581-2404028

फैक्स/Fax 91-581-2404227

Materials: 0581-2404014 IT Services: 0581-2404010 Transportation: 0581-2404571



IFFCO Website: www.iffco.in



EN-01-F-11

(Page 01 of 10)

(FORM - V)

ENVIRONMENTAL STATEMENT FOR THE FINANCIAL YEAR ENDING ON "31st MARCH 2025"

(Part - A)

I. Name and address of the owner of Industry:

Mr. Satyajit Pradhan Senior General Manager

IFFCO Aonla Unit, Paul Pothan Nagar, Post: IFFCO Township Distt: Bareilly (U.P.) Pin Code: 243403

II. Last date of Environmental Audit.

31.03.2025

III. Year of Establishment

Aonla - I

: 16.07.1988

(Start of Commercial Production) Aonla -II

: 25.12.1996 Capacity Enhancement : October, 2008

Modernization & Expansion for Production of Nano Fertiliser : 01.01.2023

(Part – B)

WATER AND RAW MATERIAL CONSUMPTION

CATEGORY WISE WATER CONSUMPTION

Table-I

Water consumption (m³/day)	Financial Year 2023-24	Financial Year 2024-25
Plant	3603.22	3395.70
Cooling water	20015.75	20157.07
Domestic	3056.59	3012.14
Miscellaneous	2486.387	2360.92

FINISHED PRODUCT

Table -II

Name of the Product	Unit	Production Capacity	
UREA	MT	2326500	
Nano Urea	KL	36500	

(Page 02 of 10)

RAW MATERIAL CONSUMPTION

Table - III

Name of Raw Material	Unit	Yearly Consumption			
		Financial Year 2023-24	Financial Year 2024-25		
(1)	(2)	(3)	(4)		
Raw Water (Plant + Cooling)	m³	8143319	8279698		
Total Raw Water	m ³	10166500	10240863		
Natural Gas	Sm ³	1386154390	1377258819		

CONSUMPTION OF RAW WATER & RAW MATERIAL PER UNIT OF FINISHED PRODUCT

Table - IV

Name of Raw material	Unit (Per MT of Urea	Consumption of Raw Material per unit of finished product			
	Production)	Financial Year 2023-24	Financial Year 2024-25		
(1)	(2)	(3)	(4)		
Raw Water (Plant + Cooling)	m ³ /MT of Urea	3.448	3.559		
Total Raw Water m³/MT of Urea		4.305	4.402		
Natural Gas	Sm ³ /MT of Urea	588.26	592.01		

(Part - C)

POLLUTION GENERATED

LIQUID EFFLUENT:

The annual average concentration of pollutants in treated effluent discharged and their percentage decrease / increase in comparison to the MINAS for the year 2024-25 are given in Table - V as below: -

Table - V

100 5.5 - 8.5 - - 10	Pollution Control Board (UPPCB) 100 5.5 - 9.0 <40.0°C	Average concentrati on of Pollutants 80.00 7.70 25.00 14.82	decrease (+)/(-) of pollutants -20.00
6.5 - 8.5 - -	Board (UPPCB) 100 5.5 - 9.0 <40.0°C	on of Pollutants 80.00 7.70 25.00	-20.00
6.5 - 8.5 - -	100 5.5 - 9.0 <40.0°C	80.00 7.70 25.00	-20.00 - -
6.5 - 8.5 - -	100 5.5 - 9.0 <40.0°C	80.00 7.70 25.00	-
6.5 - 8.5 - -	5.5 - 9.0 <40.0°C	7.70 25.00	-
-	<40.0°C	25.00	
-	<40.0°C	25.00	-
- - 10	30		-
- 10		14.82	50.00
10		14.82	
10	10		-50.60
	10	NT	-
-	absent	absent	-
			_
-	0.5	NT	
	0.4	NIT	
-	2000000		-99.60
-	5.0	0.02	-99.60
50	50	5 57	-88.86
	0.000		-95.25
			-90.59
-		Coloni to o	-55.27
			25 - 1 de 1900 (1900)
_	5.0	1.10	-78.00
_	1000	245.25	-75.48
10	-	0.39	-96.10
0.1	0.2	NA	-
	10	- 0.1 - 5.0 50 50 2.0 4.0 75 100 - 250 - 5.0 - 1000 10 -	- 0.1 NT 0.02 50 50 5.57 2.0 4.0 0.19 75 100 9.41 - 250 111.83 - 5.0 1.10 - 1000 245.25 10 - 0.39

It is emphasized from the above table – V, the average annual concentrations
of pollutants in treated liquid effluent discharged are considerably less than
the prescribed standards.

(Page 04 of 10)

- Approx 65% of the treated effluent is utilized in the irrigation of Green Belt developed in and around the plant and township in year 2024-25. The balance is let out to river Aril.
- Use of Chromate based corrosion inhibitor in cooling water treatment has been phased out since March 1999. The eco-friendly, non-chromate-based corrosion inhibitors are being used in cooling water treatment since then. Hence, there is no generation of Chromate sludge.

AIR-EMISSION:

AVERAGE VALUES OF UREA DUST EMISSION

Table-VI

Plant	Unit	Standard	Results
Urea Prill Tower Aonla –l	mg/Nm³	50	34.32
Urea Prill Tower Aonla –II	mg/Nm³	50	33.84

It is evident from the above table-VI, the annual average concentration of Particulate Matter i.e. Urea Dust in prill tower emissions is well below the prescribed limits.

STACKS MONITORING:

AVERAGE VALUES OF STACK ANALYSIS

Table -VII

Plant	Parameters	Standard	Average Values
a) Ammonia- I (Primary Reformer Stack)	NOx, mg/Nm3SOx, ppm	400 Not Prescribed	105.00 Traces
b) Ammonia- II (Primary Reformer Stack)	◆ NOx, mg/Nm3 ◆ SOx, ppm	400 Not Prescribed	100.40 Traces
c) Ammonia- II (GT-HRU Stack)	◆ NOx, ppm ◆ SOx, ppm	Not Prescribed Not Prescribed	26.25 Traces
d) SGPG Plant (Steam Generation Stack)	NOx, ppmSOx, ppm	Not Prescribed Not Prescribed	S/D S/D
e) SGPG Plant (GT-HRSG – I Stack)	NOx, ppmSOx, ppm	Not Prescribed Not Prescribed	52.69 Traces
f) SGPG Plant (GT-HRSG – II Stack)	NOx, ppmSOx, ppm	Not Prescribed Not Prescribed	49.14 Traces

It is evident from the above table – VII that the annual average concentration of Pollutants in stacks emissions are well below the prescribed standards.

(Page 05 of 10)

AMBIENT AIR MONITORING:

AVERAGE VALUES OF AMBIENT AIR ANALYSIS

Table - VIII

	Unit	NAAQS		Location				
Parameters		Standards	Ammonia	Transport	GET Hostel	Guest		
		(Annual	Storage	Office	(Township)	House		
		Average)	Area			(Township)		
PM ₁₀	μg/Nm³	60	51.90	53.91	50.24	41.92		
PM _{2.5}	μg/Nm³	40	33.37	34.74	32.37	30.38		
NH ₃	μg/Nm³	100	11.62	12.59	10.98	8.66		
SO ₂	μg/Nm³	50	5.12	5.25	5.00	4.49		
NO ₂	μg/Nm³	40	6.33	6.60	6.14	5.22		

It is evident from the above table-VIII that the annual average concentration of pollutants in Ambient Air are well below the prescribed limits of National Ambient Air Quality Standards (NAAQS).

GROUND WATER MONITORING:

The samples of ground water are collected from various locations in and around the plant and analyzed for NO_3 and Cr^{+6} . The average annual results are as follows:

Table-IX

Unit	Standard	Annual Average Analysis
mg/l	10	<0.50
mg/l	0.1	NT
	mg/l	mg/l 10

(Part-D)

HAZADOUS WASTES

As specified under Hazardous and other wastes (Management and Transboundary movement) Rules, 2016.

-	-	
Ta	h	e-X

Hazardous wast	es	Financial Year (2023-24)			Financial Year (2024-25)				
From process	Unit	Stock as on 01.04.23	Qty. Gener ated	Qty Sold	Stock as on 31.03.24	Stock as on 01.04.24	Gener ated	Qty Sold	Stock as on 31.03.25
(A) Spent oil (Reclaimed & reused/sold)	m ³	3.57	69.30	68.25	4.62	4.62	58.17	52.50	10.29
(B) Spent Catalyst	MT	4.40	387.08	391.48	Nil	Nil	Nil	Nil	Nil
(C) Empty Drums	Nos.	Nil	Nil	Nil	Nil	Ņil	400	Nil	Nil
(D) Empty Bags	MT	Nil	Nil	Nil	Nil	Nil	Nil	Nil	Nil
(E) ETP Sludge	MT	Nil	Nil	Nil	Nil	Nil	Nil	Nil	Nil
(C) Chromate sludge containing Hydroxides of Fe AI, Cr, Zn & Ca		disconti Hence,	Use of Cr+6 compounds has been discontinued since March, 1999. Hence, there is no chromate sludge formation.				ued sine	ce Marc	has been h, 1999. ite sludge

(Part-E)

COMPOSITION AND QUANTITY OF HAZARDOUS WASTES

(Please indicate composition and quantity of hazardous wastes solids & liquids with description of methodology adopted for their treatment.)

(1) SOLID HAZARDOUS WASTES

At IFFCO Aonla, the solid hazardous wastes are spent catalysts, empty drums, empty bags and ETP Sludge. Spent catalysts are generated as and when exchanged / replaced. These are being kept in sealed covered drums on cemented platforms under a shed in plant premises. Empty drums and bags are cleaned and kept in separate specified areas. Spent catalysts, empty drums & empty bags are sold to authorized recyclers. ETP Sludge when generated, shall be collected in PVC Drums and shall be sent to TSDF for disposal.

(2) LIQUID HAZARDOUS WASTES

At IFFCO Aonla, the liquid hazardous wastes are only spent lube oil. The spent lube oil is generated as and when exchanged / replaced. These are being kept in sealed covered drums on cemented platform under shed and sold to recyclers having authorisation from CPCB.

The annual statement of hazardous wastes for the year 2024-25 has been submitted to U. P. Pollution Control Board on 27.06.2025. The details of spent catalysts and spent lube oil are given in Table-X as above.

(Part - F)

COST OF POLLUTION CONTROL MEASURES PER MT OF UREA PRODUCTION DURING 2024-25

Cost of pollution control measures per MT of Urea production for the year 2024-25 is Rs. 89.22.

(Part - G)

PROPOSALS FOR YEAR 2025-26 FOR ENVIRONMENT PROTECTION WHICH IS RELATED TO POLLUTION CONTROL AND CONSERVATION OF NATURAL RESOURCES

- Plantation of minimum 6,400 tree saplings for gap filling and replacement of dead wood trees in factory and township area.
- To control urea spillage below 195 MT/month.
- To control water consumption below 4.75 m³/MT urea production.
- To produce minimum 32,000 kg of vermi-compost from Bio-degradable household solid waste and horticulture waste generated in IFFCO Aonla Township & Plant canteen.
- To recover minimum 1,48,000 MT CO₂ from stack flue gases of Ammonia Plant-I Primary Reformer through CDR unit and minimizing the emission of CO₂ into the atmosphere.
- To increase awareness on environmental issues and conservation of natural resources amongst employees, trainees, contractors' staff and other concerned persons to minimum 180 participants.
- To reduce 200 MWh annual electrical Power Consumption by replacement of conventional electrical devices with energy efficient devices and installation of new Roof Top Solar Power Plant in plant and township.
- To generate a minimum 2200 MWh Solar Power from existing Roof-top Solar Power Plants installed in Plant & Township.
- To recycle minimum 7.8 lakh M³ of treated sewage in the plant as Cooling Tower make-up.
- In compliance with EC, ETP is being upgraded by the installation of an RO-based Wastewater Treatment Plant of capacity 100 m3/hr. The treated water shall be recycled as Cooling Tower make-up water.
- More utilisation of "Treated waste water" in horticulture use.
- · Consumption of "Natural Resources more efficiently".
- Safe storage and disposal of hazardous wastes.

(Part – H)

MEASURES TAKEN FOR ENVIRONMENT PROTECTION, POLLUTION CONTROL AND CONSERVATION OF NATURAL RESOURCES IN IFFCO AONLA UNIT

The environment management systems at IFFCO Aonla aim for the abatement of pollution at the source of generation itself. The following measures are being taken regularly for pollution control, environmental protection and conservation of natural resources. The measures taken are: -

1. Zero effluent technology, based on recycling and reuse of the wastes generated in the main plants since design stage.

(Page 08 of 10)

- 2. Utilization of resources prudently so that waste generation is minimized.
- 3. Treatment of waste water containing Ammonia & Urea as contaminants generated from urea plants through Deep Urea Hydrolyser and Distillation Tower (Provided separately in both the urea plants). Recovered Ammonia and Carbon Dioxide are reused in the production of urea, whereas remaining waste water containing ammonia and urea in the range of 5-10 PPM and <1 PPM respectively is reused as Boiler Feed Water after polishing in DM Plant.
- 4. Treatment of Process Condensate from ammonia plants by Process Condensate Stripper (Provided separately in both ammonia plants) and reusing stripped process condensate as Boiler Feed Water after polishing in DM Plant.
- Reusing steam condensate from all the Ammonia & Urea plants and turbine condensate from both urea plants as Boiler Feed Water after polishing in DM Plant.
- 6. Treatment of Turbine condensates from both Ammonia Plants in A. C. Filtration & Mechanical Filtration units provided in both Ammonia plants and reusing it as Boiler Feed Water.
- 7. Collection of Oil containing water and spilled oil from the compressor houses in oil collection pit provided separately in all ammonia and urea plants. The oil is separated through "Disc Oil Separator". Reclaimed oil is sold to recyclers as per CPCB guidelines. The remaining waste water is pumped to ETP for further treatment.
- 8. Neutralization of Acidic and Alkaline waste water generated in D M Plant after regeneration of exhausted cation and anion resins in DM Plant.
- 9. Cooling water treatment is based on Eco-friendly, Non-chromate based corrosion inhibitors. Hence, there is no generation of hazardous and toxic Chromate sludge.
- 10. Treatment of occasional waste water generated during upset and startup/shutdown condition of the plants having ammonia as contaminant in Effluent Treatment Plant through Air/Steam stripping.
- 11. The treated waste water is kept stored in two nos. of LDPE lined lagoons (Guard-Ponds) of capacity 85,000 m³ each. Approx 65% of this treated effluent is used in the irrigation of green belt developed in and around plant and township; Balance is let out to river Aril through "V" notch.
- 12. Regular monitoring of quality of liquid effluent, storm drain water, ground water, stack flue gases, urea prill tower emission, ambient air by IFFCO's own laboratory. The quality of liquid effluent, gaseous emissions & ambient air is also being cross checked by an U.P. Pollution Control Board/ MoEF & CC authorised laboratory. The concentrations of pollutants always remain well below the standard limits. The reports are being submitted to regulatory authorities.
- 13. All pollution control devices in the plants are kept in perfectly good condition to control pollution. Their performances are being monitored regularly by our laboratory and plant personnel.
- 14. Provided built in safety logics and guards in the plant operations and safe shut down/start up procedures.
- 15. Education and training of employees, contractor workers etc. regarding environmental issues.

- 16. The conversion of household garbage along with plant canteen wastes, vegetable market and Horticulture wastes into "Vermi-Compost".
- 17. Hazardous wastes generated at IFFCO Aonla are spent catalysts, spent lube oil, empty drums, empty bags and ETP Sludge. Spent catalysts and spent lube oil are kept in sealed covered drums on a cemented platform under a shed in factory premises. Empty drums and bags are cleaned and kept in separate specified areas. These (spent catalysts, spent lube oil, empty drums and empty bags) are recyclable and sold to authorized recyclers. ETP Sludge when generated, shall be collected in PVC Drums and shall be sent to TSDF for disposal.
- 18. A carbon Dioxide Recovery unit (CDR) for recovering 450 MT Carbon Dioxide per day from the Ammonia Plant Primary Reformer stack flue gas was commissioned in December, 2006. During 2024-25, 175467 MT Carbon Dioxide is recovered from the stack flue gas and is utilized in the production of Urea.
- 19. Energy Saving Schemes have been implemented during the years 2005-06 to 2007-08 during turnaround of the plants without affecting the normal operations. The Energy Saving Scheme has been registered with UNFCCC as CDM project. A sum of 54,759 MT GHG emission reduction from April 2005 to April 2007 has been claimed as Voluntary Emission Reduction and a sum of US \$320340.15 has been credited to IFFCO's account on 21st April, 2008.

The reduction in GHG emission for the period 15.04.2007 to 31.12.2007 i.e. 23434 MT has been certified as Certified Emission Reduction (CER) and a sum of US \$ 158,179 credited to the IFFCO account.

- GHG Emission Reduction for the period 01.01.2008 to 30.09.2008 i.e. 33892 MT has been verified as CER and a sum of US \$ 228,771 credited in IFFCO account
- 20. IFFCO Aonla Unit has upgraded the sewage treatment system with MBR-based STP having Primary, Secondary, and Tertiary treatment units. Treated sewage is being fully recycled in the plant as cooling tower make-up water.
- 21. For the conservation of water, seven Roof-top Rain Water Harvesting Systems installed at GET Hostel, Kendriya Vidyalaya/Tiny Tots School, Hospital, Guest House/New Club, Anand Bhawan Club, Open Air Theatre & Administration Building are in operation in IFFCO Aonla. Two Rain Water Harvesting Systems have been installed for underground recharging of rain water of storm drains in the township.
- 22. Online monitoring system has been installed at IFFCO Aonla Unit for effluent quality & flow and connected to CPCB server http://cpcbrtdms.nic.in/. Online monitoring system for urea dust (PM) emission was installed on one Prill Tower on trial basis as per CPCB directions. The trial of the system was unsuccessful.
- 23. Effluent Treatment Plant is being upgraded by installation of a RO-based waste water treatment plant of capacity 100 m3/hr. The treated water shall be fully recycled in the plant as cooling tower make-up water.

(Page 10 of 10)

GREEN BELT DEVELOPMENT

Green belt has been developed all along the factory and township. The width of the green belt varies from 80 M to 250 M. Additional afforestation is being carried out every year to fill up left out area and replacement of dead wood trees in factory and township. In year 2024-25, total 9,773 saplings have been planted.

INTERNATIONAL ACCREDITATION

IFFCO Aonla Unit is certified with ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 for its Quality Management Systems (QMS), Environment Management Systems (EMS) and Occupational Health & Safety Management Systems (OHSMS) respectively by M/s QS Zurich A.G under Integrated Management System and the certificate is valid upto 11.03.2027. IFFCO Aonla Unit is also certified with ISO 50001:2018 for its Energy Management System (EnMS) by M/s BSI Group India Pvt. Ltd., New Delhi and the certificates is valid upto 17.01.2028.

ENVIRONMENTAL STATEMENT

- There is no adverse environmental impact on Eco-system due to plant operation since its inception.
- All the pollution Control devices in plants are being kept in perfectly good working condition and their performance is being monitored regularly.
- Network of irrigation pipeline of approx. 20 Kms. in plant and township to utilise treated waste water/effluent. Approx. 65% of treated effluent has been used in irrigation of green belt in and around the factory and township during 2024-25.
- Ammonia and Hydrogen detectors have been installed at crucial locations in the plants for early leak detection of leakages, if any.
- A series of lectures are being taken regularly for environmental awareness for the employees, contractor's staff, students, nearby villagers etc.

ENVIRONMENTAL AWARDS:

IFFCO Aonla has won many awards in the field of Environment. The awards won during last five years are as under: -

- FAI Environmental Protection Award- Special Award-2024 (winner) for IFFCO Aonla Unit from the Fertilizer Association of India.
- FAI Environmental Protection Award 2022-23 (winner) for Nitrogenous Fertiliser Plant from The Fertilizer Association of India.
- FAI Environmental Protection Award 2021-22 (Winner) for a Nitrogenous Fertilizer Plant from The Fertiliser Association of India.
- "CII National Awards for Excellence in Water Management" for the year 2020 for outstanding work on water resource management.
- 20th Annual Greentech Environment Award-2020 (Winner Award) in Fertiliser sector from Greentech Foundation, New Delhi, for outstanding achievement in Environment Management.